

SECTION 1. PRODUCT IDENTIFICATION

1.1 TRADE NAME (AS LABELED):**Skinister Medical Adhesive**SYNONYMS:

SA1D, SA2S, SA4S

CAS#:

Mixture

1.2 PRODUCT USE:

To temporarily adhere appliances to skin, such as ostomy pouches, breast forms, and condom catheters.

1.3 MANUFACTURER'S NAME:**Delta Molding LLC**ADDRESS:

1233 East Beamer St, Ste G, Woodland, CA 95776

BUSINESS PHONE:

1(888) 967-4273

EMAIL:

Info@SkinisterMedical.com

1.4 SUPPLIER'S NAME:**Premier Ostomy Centre Inc**ADDRESS:

6607 Chem. de la Côte-des-Neiges, Montréal, QC H3S 2B3, Canada

BUSINESS PHONE:

+1 514-940-9666

1.5 EMERGENCY PHONE NUMBERS:

Infotrac, 1-800-535-5053 (North America)

Infotrac, +1-352-323-3500 (International)

DATE OF PRIOR REVISION:

New

DATE OF LATEST REVISION:

February 2, 2025

SECTION 2. HAZARD IDENTIFICATION

2.1 GHS LABELING AND CLASSIFICATION:

This product meets the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 and regulation (EU) No. 2020/878 and regulation (EC) No. 1272/2008.

Index Number:

EC# 203-492-7 is not listed in Annex VI

Substances not listed either individually or in group entries must be self-classified.

Component(s) Contributing to Classification(s)

Hexamethyldisiloxane

2.2 LABEL ELEMENTS

GHS Hazard Symbol(s)

Signal Word: **Danger!****GHS Hazard Classification(s):**

Flammable Liquid Category 2

Aquatic Acute Category 1

Aquatic Chronic Category 2

Hazard Statement(s):

H225 Highly flammable liquid and vapour

H400 Very toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects

Prevention Statement(s):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response Statement(s):

P303+P361+P353 IF ON SKIN (or hair) Take off immediately all contaminated clothing. Rinse skin with water.
 P370+P378 In case of fire: Use media defined in Section 5 to extinguish.
 P391 Collect spillage

Storage Statement(s):

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal Statement(s):

P501 Dispose of contents/container in accordance with local/ regional/ national/ international regulations.

2.3 OTHER HAZARDS:

Endocrine Disruptor Information: This product does not contain chemicals on the Candidate List of substances of very high concern for Authorisation.

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS#	EINECS #	Hazard Classification
Hexamethyldisiloxane	65-85%	107-46-0	203-492-7	Flam Liq 2

SECTION 4. FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing for at least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT: Seek medical advice if serious irritation occurs. However, the product is designed to be skin-safe with normal use, and adhesive residue may be removed from skin with Skinister Medical Adhesive Remover or isopropyl alcohol.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION: Rinse mouth thoroughly with water and drink a small amount of milk, if available, to help dilute the substance. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek immediate medical attention if more than a tablespoon was ingested, and take a copy of the label and/or Safety Data Sheet (SDS) with the victim to the health professional. Serious illness is unlikely in the event of smaller ingestion amounts

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing eye problems may be aggravated by prolonged contact.

4.2 SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Contact with eyes may cause temporary irritation

4.3 RECOMMENDATIONS TO PHYSICIANS:

Treat symptoms and eliminate overexposure.

SECTION 5. FIRE-FIGHTING MEASURES

5.1 FIRE EXTINGUISHING MATERIALS:

Use fire extinguishing methods below:

Water Spray:	No	Carbon Dioxide:	Yes
Foam:	Yes	Dry Chemical:	Yes
Halon:	Yes	Other:	N/A

5.2 UNUSUAL FIRE AND EXPLOSION HAZARDS:

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Explosion Sensitivity to Mechanical Impact: No

Explosion Sensitivity to Static Discharge: Yes

5.3 SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Provide adequate ventilation. Wear suitable protective clothing, gloves and eye/face protection. For large spills, or when multiple containers are involved, evacuate personnel to safe areas.

6.2 ENVIRONMENTAL PRECAUTIONS:

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3 SPILL AND LEAK RESPONSE:

Wipe up small spills with absorbent materials such as paper towels or rags. Remove remaining adhesive residue with Skinister Medical Adhesive Remover or isopropyl alcohol. For large spills, provide diking or other appropriate containment to keep material from spreading. If the dike can be pumped, store recovered material in appropriate container. Clean up remaining materials from the spill with suitable absorbent.

SECTION 7. HANDLING and STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Flammable. Do not spray on a flame or any incandescent material, electrical appliance or source of heat. Keep away from sources of ignition - No Smoking. Keep out of the reach of children. Avoid spraying into eyes. Do not apply to open wounds or mucous membranes. Discontinue use if irritation occurs. Avoid inhalation of vapor or mist. Take care to prevent spills, waste and minimize release to the environment.

7.2 STORAGE AND HANDLING PRACTICES:

Keep away from incompatible materials. Keep in a dry, well-ventilated area in closed containers. Protect containers from physical damage. Keep container tightly closed and sealed until ready for use. Store in accordance with local regulations.

7.3 SPECIFIC USES:

Medical Adhesive. Intended to temporarily adhere appliances to skin, such as ostomy pouches, breast forms, and condom catheters.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 EXPOSURE PARAMETERS:

Chemical Name	CAS#	ACGIH TLV	OSHA TWA	EH40 TWA
Hexamethyldisiloxane	107-46-0	Not Listed	Not Listed	Not Listed

8.2 EXPOSURE CONTROLS:

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Not required for properly ventilated areas. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Not required for normal use. Wear safety glasses when handling larger quantities, when splashing is possible, and when applied near the face. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

HAND PROTECTION: Not required for normal use. Chemical resistant gloves are required when handling larger quantities and spills. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

BODY PROTECTION: Not required for normal use. Use body protect appropriate to task being performed. If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

SECTION 9. PHYSICAL and CHEMICAL PROPERTIES**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:**

APPEARANCE (Physical State) and COLOR: This product is a colorless liquid

ODOR: None

ODOR THRESHOLD: Not Available

pH: Not Available

MELTING/FREEZING POINT: -50°C (-58°F)

BOILING POINT: 100-101°C (212-214°F)

FLASH POINT: -1°C (Method: closed cup)

FLAMMABILITY (SOLID, GAS): Not Applicable

UPPER/LOWER FLAMMABILITY OR EXPLOSION LIMITS: 0.8% / 7.0% by volume in air.

VAPOR PRESSURE (mm Hg @ 20°C (68°F): 0.1 mm Hg at 20°C (68°F)

VAPOR DENSITY: 5.8

RELATIVE DENSITY: 0.84

SPECIFIC GRAVITY: 0.845 at 25°C (77°F)

SOLUBILITY IN WATER: Insoluble

WEIGHT PER GALLON: 7.01 lbs/gallon

PARTITION COEFFICIENT (n-octanol/water): Not Available

AUTO-IGNITION TEMPERATURE: 410°C (770°F)

DECOMPOSITION TEMPERATURE: Not Available

VISCOSITY: 25-50 cP

9.2.1 INFORMATION WITH REGARD TO PHYSICAL HAZARD CLASSES

EXPLOSIVES: Not Classified as an Explosive

FLAMMABLE GASES: Flammable Vapors

AEROSOLS: Not Classified as an Aerosol

OXIDISING GASES: Not Classified as an Oxidizing Gas

GASES UNDER PRESSURE: Not Applicable, Not Under Pressure

FLAMMABLE LIQUIDS: Class 3 Flammable Liquid

FLAMMABLE SOLIDS: Fully Dry Solids Are Not Flammable

SELF-REACTIVE SUBSTANCES AND MIXTURES: Not Available

PYROPHORIC LIQUIDS: Not Classified as a Pyrophoric Liquid

PYROPHORIC SOLIDS: Not Classified as a Pyrophoric Solid

SELF-HEATING SUBSTANCES AND MIXTURES: Not Available

SUBSTANCES AND MIXTURES, WHICH EMIT FLAMMABLE GASES IN CONTACT WITH WATER: Not Available

OXIDISING LIQUID: Not Classified as an Oxidizing Liquid

OXIDISING SOLID: Not Classified as an Oxidizing Solid

ORGANIC PEROXIDES: Not Classified as an Organic Peroxide

CORROSIVE TO METALS: Not Corrosive

DESENSITISED EXPLOSIVES: Not Classified as a Desensitized Explosive

GASES UNDER PRESSURE: Not Available

9.2.2 OTHER SAFETY CHARACTERISTICS

MECHANICAL SENSITIVITY: Not Sensitive

SELF-ACCELERATING POLYMERISATION TEMPERATURE: Not Available

FORMATION OF EXPLOSIBLE DUST/AIR MIXTURES: Not Applicable

ACID/ALKALINE RESERVE: Neutral

EVAPORATION RATE: Not Available

MISCIBILITY: Insoluble in Water

CONDUCTIVITY: Not Conductive

CORROSIVENESS: Not Corrosive

GAS GROUP: Not Applicable

REDOX POTENTIAL: Not Available

RADICAL FORMATION POTENTIAL: Not Available

PHOTOCATALYTIC PROPERTIES: Not Available

SECTION 10. STABILITY and REACTIVITY

10.1 REACTIVITY:

No specific test data related to reactivity available for this product or its ingredients.

10.2 STABILITY:

Stable under conditions of normal storage and use.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. Safe handling conditions may be maintained by keeping vapor concentrations within the occupational exposure limit for formaldehyde. See OSHA formaldehyde standard, 29 CFR 1910.1048 Formaldehyde may cause cancer. It is also toxic by inhalation, skin absorption and ingestion, corrosive to skin and eyes, and may cause skin sensitization and respiratory irritation.

10.4 CONDITIONS TO AVOID:

Handling operations that can promote accumulation of static charges. Heat, flames and sparks..

10.5 MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:

Oxidizing agents.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

TOXICITY DATA:

Hexamethyldisiloxane

Acute oral toxicity LD50 (Rat): >16 ml/kg
 Assessment: The substance or mixture has no acute oral toxicity
 Remarks: On basis of test data.

Acute inhalation toxicity LC50 (Rat): 15956 ppm
 Exposure time: 4 h
 Test atmosphere: vapor
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: On basis of test data.

Acute dermal toxicity LD50 (Rat): > 2,000 mg/kg
 Assessment: The substance or mixture has no acute dermal toxicity
 Remarks: On basis of test data.

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Based on available data, the classification criteria are not met
Serious eye damage / irritation	Based on available data, the classification criteria are not met
Respiratory or skin sensitization	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

SUSPECTED CANCER AGENT: Ingredients within this product are not found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

REPRODUCTIVE TOXICITY INFORMATION: No specific information is available concerning the effects of this product and its components on the human reproductive system.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE: Data not sufficient for classification.

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE: Data not sufficient for classification.

ASPIRATION HAZARD: Data not sufficient for classification.

OTHER DATA: This material contains hexamethyldisiloxane (HMDS). Repeated inhalation exposure in rats to HMDS resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

11.2 INFORMATION ON OTHER HAZARD CLASSES WHICH RELATES TO ENDOCRINE DISRUPTING PROPERTIES:

No specific data available for this product.

SECTION 12. ECOLOGICAL INFORMATION

12.1 TOXICITY:

Hexamethyldisiloxane

Toxicity to fish

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.37 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.46 mg/l

Exposure time: 96 h

Remarks: On basis of test data.

Toxicity to algae

EC50 (Selenastrum capricornutum (green algae)): > 0.55 mg/l

Remarks: No toxicity at the limit of solubility.

On basis of test data.

M-Factor

1

Toxicity to daphnia and

other aquatic invertebrates

NOEC (Daphnia): 0.32 mg/l

Exposure time: 21 d

NOEC (Daphnia magna (Water flea)): 0.1 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: On basis of test data.

12.2 PERSISTENCE AND DEGRADABILITY:

Hexamethyldisiloxane

Bioaccumulation

Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 2,410

Concentration: 0.04 mg/l

Remarks: On basis of test data.

Partition coefficient:

noctanol/water

log Pow: 5.06 (20 °C)

Remarks: On basis of test data.

12.3 BIOACCUMULATIVE POTENTIAL:

No specific data available on this product.

12.4 MOBILITY IN SOIL:

No specific data available on this product.

12.5 RESULTS OF PBT AND vPvB ASSESSMENT:

No specific data available on this product.

12.6 ENDOCRINE DISRUPTING PROPERTIES:

No specific data available on this product.

12.7 OTHER ADVERSE EFFECTS:

No specific data available on this product.

12.8 WATER ENDANGERMENT CLASS:

May be water endangering in accordance with EU Guideline 91/155-EWG. Do not allow product to reach ground water, water course or sewage system. At present there are no ecotoxicological assessments for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS:

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, as well as those of Canada, Australia, EU Member States and Japan.

Resource Conservation and Recovery Act (RCRA): This product is classified as a RCRA hazardous waste due to its flammable solvent content.

Disposal of Liquid Adhesive and Empty Containers: Liquid adhesive contains flammable solvents and must be treated as hazardous waste. Even empty containers retain flammable residue and should not be exposed to heat, flames, sparks, or other ignition sources. Dispose of unused liquid adhesive and empty containers at an approved hazardous waste disposal facility.

Alternative Disposal Method for Small Quantities: Small quantities may be disposed of as non-hazardous waste only when fully dry. Dispense remaining adhesive onto cardboard or paper towels, and allow it to dry completely in a well-ventilated area away from ignition sources. Dispose of the dry adhesive as non-hazardous waste. Open the container by removing the threaded cap and ensure any residue dries completely. Once dry, dispose of the container as non-hazardous waste.

13.2 WASTE CODE:

D001: Ignitability

SECTION 14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

14.1 U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN IDENTIFICATION NUMBER: UN1993
PROPER SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)
HAZARD CLASS NUMBER and DESCRIPTION: 3
PACKING GROUP: II
DOT LABEL(S) REQUIRED: Flammable Liquid
NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128
MARINE POLLUTANT: The components of this product are designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is considered as dangerous goods.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO):

UN IDENTIFICATION NUMBER: UN1993
PROPER SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)
HAZARD CLASS NUMBER and DESCRIPTION: 3
PACKING GROUP: II

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.

SECTION 15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA 311/312: Flammable (gases, aerosols, liquids, or solids)
 Hazard not otherwise classified (physical hazards)

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ):

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	*
Ethylbenzene	100-41-4	1000	*

* Calculated RQ exceeds reasonably attainable upper limit.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory or are exempted from listing.

OTHER U.S. FEDERAL REGULATIONS: None known

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

15.2 CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: Components are DSL Listed, NDSL Listed and/or are exempt from listing

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This product has been classified per WHMIS 2015.

15.3 EUROPEAN ECONOMIC COMMUNITY INFORMATION:

This product does meet the definition of a hazardous substance or preparation as defined by regulation (EU) No. 2020/878 and regulation (EC) No. 1272/2008.

CHEMICAL SAFETY ASSESSMENT :

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

<p>HMIS Rating (Scale 0-4) Health hazard: 0 Flammability: 3 Physical Hazard: 0</p>	<p>NFPA Rating (Scale 0-4) Health hazard:0 Flammability: 3 Physical Hazard: 0</p>
--	---

Abbreviations and acronyms

ACGIH	<i>American Conference of Governmental Industrial Hygienists</i>
CFR	<i>Code of Federal Regulations</i>
DOT	<i>Federal Department of Transportation</i>
GHS	<i>The Globally Harmonized System of Classification and Labelling of Chemicals</i>
HMIS	<i>Hazardous Material Identification System</i>
HCS	<i>Hazard Communication Standard</i>
IARC	<i>International Agency for Research on Cancer</i>
IATA	<i>The International Air Transport Association</i>
ICAO	<i>The International Civil Aviation Organization</i>
IMDG	<i>International Maritime Dangerous Goods</i>
IMO	<i>International Maritime Organization</i>
LD50/LC50	<i>Lethal Concentration/Dose, 50 percent</i>
NFPA	<i>National Fire Protection Association</i>
NIOSH	<i>National Institute for Occupational Safety and Health</i>
NTP	<i>National Toxicology Program</i>
OSHA	<i>Occupational Safety and Health</i>
PEL	<i>Permissible Exposure Limit</i>
SARA	<i>Superfund Amendments and Reauthorization Act</i>
TLV	<i>ACGIH Threshold Limit Value</i>
TWA	<i>Time-Weighted Average</i>

PREPARED BY: Chris Eigbrett

MSDS to GHS Compliance
www.MSDStoGHS.com

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. Delta Molding LLC assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are no adhered to as stipulated in the data sheet. Furthermore, Delta Molding LLC assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.

REVISION HISTORY

February 2, 2025 - Document review / update

END OF SDS SHEET